

• 不锈钢丝

STAINLESS STEEL STRIP

EUROPE	CHINA	JAPAN (JIS)	US
1.4310	1Cr17Ni7	SUS 301	301
1.4310 Mo	-	-	301 Mo
1.4301	0Cr19Ni9	SUS 304	304
1.4401	6Cr17Ni12Mo2	SUS 316	316
1.4568	0Cr17Ni7Al	SUS 631	631
1.4006	12Cr13	SUS410	410
1.4021	20Cr13	SUS420J1	420
1.4016	10Cr17	SUS430	430
1.4372	-	SUS201	201
1.4373	-	SUS202	202

交货状态 Supply condition	退火线 Annealed	表面处理:轻拉或者亮面	2B or 2R/BA
	冷拉线 Cold rolled	交货状态:硬拉,且光亮	Tempered: TR/TH
		抗拉强度700至2100兆帕	- EN 10151 From C700 to C2100
		低硬,半硬,冷硬,特硬	- YB/T 5310 From DY to TY
		1/2硬至硬,或客户要求	- JIS 4313 From 1/2H to SEH
		1/4硬至硬	- ASTM A666 From 1/4H to FH

产品以单卷或者复卷式形式交货      Single or oscillated wounded coils delivery possible.

